

THIS PAGE IS INSERTED BY OIPE SCANNING

IMAGES WITHIN THIS DOCUMENT ARE BEST AVAILABLE COPY AND CONTAIN DEFECTIVE IMAGES SCANNED FROM ORIGINALS SUBMITTED BY THE APPLICANT.

DEFECTIVE IMAGES COULD INCLUDE BUT ARE NOT LIMITED TO:

BLACK BORDERS

TEXT CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT

ILLEGIBLE TEXT

SKEWED/SLANTED IMAGES


COLORED PHOTOS

BLACK OR VERY BLACK AND WHITE DARK PHOTOS



GRAY SCALE DOCUMENTS


**IMAGES ARE BEST AVAILABLE COPY.
RESCANNING DOCUMENTS *WILL NOT*
CORRECT IMAGES.**





VOLUME
ONE

FOUNDATION DATA STRUCTURES

[illegible]



C+ OBJECTS



VOLUME 1 PRODUCT FEATURES

- *Trees, Linked-Lists, Dynamic Arrays, Graphs, Strings, Dates, Objects, Classes*
- *Object-oriented design and implementation*
- *Written entirely in C*
- *Derive your own object types: Symbol Tables, Graphical Object Lists, Pars Trees, etc.*
- *Professional, fully tested code*
- *Advanced, multi-level exception-handler speeds coding and debugging*
- *Educational tool for data structures, object-oriented programming techniques and software engineering*

OOP FEATURES


- *Each "class" is a C structure with related functions*
- *Objects are fully encapsulated*
- *Static and dynamic binding of "messages"*
- *New classes can "inherit" functionality and data from multiple object types*
- *Object-oriented compiler structures*

WHAT'S INCLUDED

- 14 types of object, over 300 functions
- User's Guide explains object-oriented programming techniques, deriving your own object types, and includes tutorials
- Reference Guide with detailed information on each object type and function
- Demo and example programs
- Full source code available as option
- Debugging and production versions of libraries
- Support hot-line
- 30 day, money back guarantee



***C+OBJECTS™ is a portable,
object-oriented C function
library used to reduce
the investment required
to build complex software.***



**What can C+OBJECTS
do for me?**

It can give you more creative time to design programs because you'll spend less time coding and debugging them. That's because the fundamental data structures used in many programs have already been built for you. Volume 1 includes data structures such as **doubly-linked lists, trees, dynamic arrays and graphs**. Volume 2 includes additional data structures such as **outlines, hash tables, stacks and queues** (details on Volume 2 appear in a separate brochure).

Your programs will be more reliable with the sophisticated, multi-level exception-handler and debug libraries. You also get Julian (date) and String object

oriented format. The Julian routines have many calculations not available in other products.

**Can C+OBJECTS data
structures be custom-
ized?**

That's the whole idea! Customizing and extending the functions of C+OBJECTS data structures is simple. Just "inherit" functionality from one or more C+OBJECTS data structures and add your own code and data on top.


For example, you could use the Tree data structure as the foundation for a parse tree. Or you might build a data structure for maintaining a graphical display list using the Doubly-Linked List object type. If you were building a data-flow diagram editor as part of a CASE package,

you would find Graph, Vertex, and Edge well suited to the task. The uses for C+OBJECTS structures are virtually unlimited!

Customizing or extending C+OBJECTS object types does not involve modifying or recompiling the C+OBJECTS code or structures. C+OBJECTS would not be a useful tool otherwise.

**What do you mean by
an "object-oriented"
function library?**

Just as structured programming and structured design principles are not language dependent, neither are the principles of object-oriented programming. When we designed C+OBJECTS, we took the fundamental object-oriented programming techniques and applied them to C. Other object-oriented



tools for C have mimicked the Smalltalk implementation, complete with all of Smalltalk's faults and inefficiencies—we didn't, we married the best of both worlds.

And Performance?

C+OBJECTS is written entirely in C and does not use pre-processors or interpreters. Performance is what sets C+OBJECTS apart from the others.

C+OBJECTS provides macros for many functions. This gives you all the advantages of encapsulation without the performance penalty of calling a function to do a simple task.

Additionally, the messaging and inheritance features are implemented in a manner *tailor-made for C*. The result is cleaner and more efficient than Smalltalk's mechanisms.

Can it help me debug my programs faster?

Yes! C+OBJECTS advanced debugging features allow you to create *reliable* programs and do so easier and more quickly than you thought possible.

First, C+OBJECTS uses function prototypes to catch simple errors at compile time involving incorrect type, wrong ordering or wrong number of parameters.

Second, C+OBJECTS can detect when it is being passed a NULL or uninitialized pointer, pointers to the wrong type, or pointers to structures which have been "garbaged". It also checks for illegal values in other parameters types.

Third, C+OBJECTS includes an advanced exception handler package. With it, you can set up a single (or multiple level) exception handler which traps exceptions generated by C+OBJECTS functions.



If an exception is raised, you can determine the type and where it occurred. You can then recover from the exception or abort, depending on which is most appropriate. Exception handlers can allow your program to be well behaved, even in the presence of bugs.

This advanced error detection technique can be used in your own code as well. No longer do your programs need to check status codes after each function call. This results in less coding yet more reliable programs.

Once your program has been debugged, you can use C+OBJECTS Production Libraries with macro functions. This eliminates most or all of the debugging checkpoints.

What else can it do to increase my productivity?

C+OBJECTS goes beyond conventional function libraries by supplying a complete set



of *object-oriented control-structures*.

These functions allow you to traverse data structures *without* having to use for, while, or do-while statements.

Control-structure functions simplify programs and eliminate a large number of potential errors — boundary conditions in loops for example.

Control-structure functions call a function of your choice for each item traversed. You can “inherit” these control-structure functions in your own data structures or create your own.

How portable is C+OBJECTS?

C+OBJECTS was designed for portability to any operating system. Expect to see versions for Windows, OS/2, Presentation Manager, and Macintosh soon.

Is it suitable as an educational tool?

Yes. As an educational aid, it can teach you the principles of object-oriented programming. The User's Guide explains object-oriented programming and the differences between C+OBJECTS and Smalltalk. It could even be used as a primer for C programmers who wish to understand more about Smalltalk.

It can teach students the concepts of abstract data types and basic data structures. The linked list, tree, and graph types could form the foundation for a data structures class.

A software engineering course would benefit from a study of C+OBJECTS. It demonstrates good design principles, strict naming and portability conventions, and *defensive programming* techniques.

But don't let this fool you into thinking C+OBJECTS is *only* of

educational value.


C+OBJECTS is a serious development tool for professionals.


What about source code, royalties etc.?

Full source code is available as an option. You will get more educational value out of C+OBJECTS with the source, but you don't need it to fully use or understand the product. Source will of course be necessary if you are porting C+OBJECTS to a new environment — call us first though, we may be able to help.

There are no royalties on programs developed using C+OBJECTS Volumes 1 or 2 and we do not require you to reproduce our copyright notice on your programs.

Call us for information on volume pricing, site licensing, and educational discounts.





Class


A **Class (Cls)** implements the object-oriented properties inheritance and messaging. It is used to subclass another object type. (See also **Object** page 11)


Doubly Linked List

A **Doubly-Linked List (Dll)** object is used to represent the head and tail of a linked list. A **Dll** contains objects of type **List Element** (or derivative objects). (See also **List Element** page 10)

ClsDefaultInit	Initialize using defaults
ClsDestroyObj	Deallocate object
ClsGetClientOffset	Return client offset
ClsGetGpMsgFunc	Return (ptr.) message function ptr.
ClsGetMsgFunc	Return (int) message function ptr.
ClsInit	Initialize the class
ClsNewObj	Allocate object
ClsSetClientOffset	Set client offset
ClsSendObjMsg	Send message, return int
ClsSendObjGpMsg	Send message, return pointer

DllAppend	Append element(s) to list
DllAppendLast	Append element(s) to end of list
DllAppendOne	Append one element to list
DllAsObj	Return list as object
DllClear	Clear list
DllClient	Return client of list
DllClientDo	Do function: all elements
DllClientDoBkws	Do function: elements backwards
DllClientCount	Do function: count elements
DllClientFind	Do search function: all elements
DllClientFirst	Return client of first element
DllClientGetNth	Return Nth client
DllClientOrNull	Return client or null
DllClientLast	Return client of last element
DllCut	Cut element(s) from list
DllCutAll	Cut all elements from list
DllCutOne	Cut one element from list
DllDeInit	Deinitialize list
DllDestroy	Deinitialize list, free space
DllGetFirst	Return first element
DllGetLast	Return last element
DllGetNth	Return Nth element
DllIsEmpty	Is list empty?
DllInit	Initialize list
DllInsert	Insert element(s) in list






Doubly Linked List


Dynamic Pointer Array

Dynamic Pointer Arrays (Dpa) are useful for storing arrays of pointers to objects of any type. A Dpa is dynamic because storage for the array is allocated and reallocated dynamically as the size of the array changes



<i>DllInsertFirst</i>	Insert elements first
<i>DllInsertOne</i>	Insert element in list
<i>DllMakeFirst</i>	Make element first
<i>DllMakeLast</i>	Make element last
<i>DllNew</i>	Initialize list object, allocate space

<i>DpaAppend</i>	Append an element
<i>DpaCut</i>	Delete element(s)
<i>DpaClear</i>	Clear dynamic array
<i>DpaCountTrueReturns</i>	Do function: count True returns
<i>DpaDeInit</i>	Deinitialize dynamic array
<i>DpaDestroy</i>	Deinitialize object, free all memory
<i>DpaDo</i>	Do function: all elements
<i>DpaDoRange</i>	Do function: range of elements
<i>DpaDoRangeCheckRet</i>	Do function: range, check return
<i>DpaDoRegion</i>	Do function: region of elements
<i>DpaDoSelfAndSuccessors</i>	Do function: successors
<i>DpaFindBkwd</i>	Find index returning True
<i>DpaFindFrwd</i>	Find index returning True
<i>DpaFindPtrBkwd</i>	Find index with matching pointer
<i>DpaFindPtrFrwd</i>	Find index with matching pointer
<i>DpaFindRangeFrwd</i>	Find index returning True for range
<i>DpaFindRangeBkwd</i>	Find index returning True for range
<i>DpaGetLast</i>	Return last element in array
<i>DpaGetNth</i>	Return Nth array element
<i>DpaGetSize</i>	Return number of elements
<i>DpaInit</i>	Initialize dynamic array object
<i>DpaLoad</i>	Load array by looping function
<i>DpaMakeElementsZero</i>	Make range of elements null
<i>DpaNew</i>	Initialize object and allocate space
<i>DpaPaste</i>	Paste element(s) into array
<i>DpaScrollDown</i>	Scroll down N lines in array
<i>DpaScrollUp</i>	Scroll up N lines in array
<i>DpaSetNth</i>	Set Nth element of array
<i>DpaSetSize</i>	Set array size to N elements



Edge

An *Edge (Edg)* is used to represent a directed edge in a Graph (Grf). An edge can be connected and disconnected from two vertices (Vtx). An edge can belong to a single graph. (See also Vertex page 14 and Graph page 9)

Exception

An *Exception (Exc)* is a container for error/status information used when a program wants to raise an exception. An *Exc* contains the type of error, its location, and other pertinent information. Exceptions are invoked via a Thread (Thr). (See also Threads page 12)

<i>EdgClientDo</i>	Do function: edge
<i>EdgConnectToVertices</i>	Connect edge to vertices
<i>EdgConnectToGrf</i>	Connect edge to graph
<i>EdgCompareInVtx</i>	Compare vertex to incoming edge
<i>EdgCompareOutVtx</i>	Compare vertex with outgoing edge
<i>EdgDeInit</i>	Deinitialize the edge object
<i>EdgDisconnectFromGrf</i>	Disconnect edge from graph
<i>EdgGetClient</i>	Return client of edge
<i>EdgGetGraphLel</i>	Return as graph list element
<i>EdgGetGrf</i>	Return graph
<i>EdgGetInLel</i>	Return incoming edge list element
<i>EdgGetInVtx</i>	Return incoming vertex
<i>EdgGetNextIn</i>	Return next incoming edge
<i>EdgGetNextOut</i>	Return next outgoing edge
<i>EdgGetOutLel</i>	Return outgoing edge list element
<i>EdgGetOutVtx</i>	Return outgoing vertex
<i>EdgGetVertices</i>	Return vertices to edge
<i>EdgInit</i>	Initialize the edge object
<i>EdgInGrf</i>	Is edge in graph?
<i>EdgNew</i>	Initialize edge object and allocate
<i>EdgSendDestroy</i>	Send message for vertex destruction
<i>EdgUpdateInVtx</i>	Replace incoming vertex
<i>EdgUpdateOutVtx</i>	Replace outgoing vertex

<i>ExcClear</i>	Clear exception
<i>ExcDeInit</i>	Deinitialize exception
<i>ExcDestroy</i>	Deinitialize exception, free space
<i>ExcGetCode</i>	Return error code
<i>ExcGetFile</i>	Return file where error detected
<i>ExcGetLine</i>	Return line where error detected
<i>ExcGetOpSysErr</i>	Return system error code
<i>ExcGetType</i>	Return type of error
<i>Exclnit</i>	Initialize exception
<i>ExcIsFatal</i>	Is exception non-recoverable?
<i>ExcNew</i>	Initialize exception, allocate space
<i>ExcSet</i>	Set exception fields




Graph


A **Graph (Grf)** object is used to represent a directed graph (or digraph) as understood by graph theory. A Graph is a collection of Vertices (Vtx) and (directed) Edges (Edg). A graph can be sorted topologically to determine if it is acyclic. (See also Vertex page 14 and Edge page 8)

Julian Date

A **Julian Date (Jul)** is used to represent a specific day in a specific year. The representation is purposely made explicit by its name. This representation of dates is most appropriate when date calculations are of more interest than formatting.



GrfAddEdg	Add edge to graph
GrfAddVtx	Add vertex to graph
GrfClear	Clear the graph
GrfCountEdg	Count edges of graph
GrfCountVtx	Count vertices of graph
GrfDestroy	Deinitialize graph and free space
GrfDeInit	Deinitialize graph object
GrfDoEdgClient	Do function: edges
GrfDoVtxClient	Do function: vertices
GrfDoVtxInTopOrder	Do function: vertices in topological order
GrfInit	Initialize graph object
GrfNew	Initialize graph allocate space
GrfRemoveEdg	Remove edge from graph
GrfRemoveVtx	Remove vertex from graph
GrfTopologicalSort	Do topological sort of graph
JulAddDays	Add/subtract days to date
JulAddDaysL	Add/subtract days to date (long)
JulAddMonths	Add/subtract months to date
JulAddQuarters	Add/subtract quarters to date
JulAddYears	Add/subtract years to date
JulToCalendar	Julian day to day, month, year
JulCopy	Copy julian day
JulDateStrToJulian	Date string to julian day
JulDaysInMonth	Days in month
JulDaysInQuarter	Days in quarter
JulDaysInYear	Days in year
JulDayOfYear	Day number in year
JulDayOfWeek	Day number in week
JulDiff	Days between two dates
JulDiffL	Days between two dates (long)
JulFromCalendar	Day, month, year to julian
JulGetMaxValue	dayReturn maximum julian value
JulGetSystemJulianDay	System date as julian day
JulInit	Initialize object
JulIsLeapYear	Is date in leap year?
JulIsMaxValue	Is date maximum julian value?



Julian Date

A Julian Date (Jul) is used to represent a specific day in a specific year. The representation is purposely made explicit by its name. This representation of dates is most appropriate when date calculations are of more interest than formatting. (Continued from page 9)

List Element

A List Element (Lel) object is used to maintain membership in a doubly-linked list (Dll). A Lel knows its previous and next list elements and the list it belongs to, if any. (See also Doubly-Linked List page 6)

<i>JulMax</i>	The maximum of two julian dates
<i>JulMin</i>	The minimum of two julian dates
<i>JulMonthDayDiff</i>	Days between date and day/month
<i>JulMonthString</i>	Fill string with month and year
<i>JulQuarterString</i>	Fill string with quarter and year
<i>JulSameDayMonth</i>	Are dates same day and month?
<i>JulSetMaxDate</i>	Set date to maximum value
<i>JulToDateStr</i>	Fill date string with specified format
<i>JulValidateDate</i>	Validate date passed as string
<i>JulWeekString</i>	Fill string with week
<i>JulYearString</i>	Fill string with year

<i>LelAppend</i>	Append element(s) to list
<i>LelAsObj</i>	Return element as object
<i>LelClientDll</i>	Return client of list
<i>LelClientNext</i>	Return client of next element
<i>LelClientPrev</i>	Return client of previous element
<i>LelClientCountSelfAndSuccessors</i>	Return count of successors
<i>LelClientDoSelfAndPredecessors</i>	Do function: predecessors
<i>LelClientDoSelfAndSuccessors</i>	Do function: successors
<i>LelClientDoPredecessors</i>	Do function: predecessors
<i>LelClientDoSuccessors</i>	Do function: successors
<i>LelClientDoRange</i>	Do function: range
<i>LelClientFindRange</i>	Do search function: range
<i>LelCount</i>	Count elements
<i>LelCut</i>	Cut element(s) from list
<i>LelDeInit</i>	Deinitialize list element object
<i>LelDoRange</i>	Do function: for range
<i>LelElementsAreInOrder</i>	Are two elements in order?
<i>LelGetClient</i>	Return client
<i>LelGetDll</i>	Return list object is in
<i>LelGetNthSuccessor</i>	Return Nth successor element
<i>LelGetNext</i>	Return next element
<i>LelGetPrev</i>	Return previous element
<i>LelInit</i>	Initialize list element object
<i>LelInList</i>	Is element in list?
<i>LelInsert</i>	Insert element(s) to list
<i>LelMakeList</i>	Make elements into list

Object

An *Object (Obj)* implements the object-oriented properties of inheritance and messaging. It is of use for implementing reusable data types (as opposed to application-specific types). (See also *Class* page 6)

String

The *String (Str)* class is used to represent null terminated character arrays.

Task

A *Task (Tsk)* object is used to represent a program. A *Tsk* owns all the threads in that task (one in MS-DOS). A task contains information used to invoke the program and other global information which belongs to a task. (See also *Thread* page 12 and *Exception* page 8)

<i>ObjDeInit</i>	Deinitialize object
<i>ObjDestroyClient</i>	Deallocate object
<i>ObjGetClientOrNull</i>	Return client
<i>ObjGetGpMsgFunc</i>	Return (ptr.) message function
<i>ObjGetMsgFunc</i>	Return (int) message function
<i>ObjGetClient</i>	Return client of subclass
<i>ObjInit</i>	Initialize object
<i>ObjSetClient</i>	Set client
<i>ObjSendClientGpMsg</i>	Send client a (ptr.) message
<i>ObjSendClientMsg</i>	Send client a (int) message

<i>StrAsMediumInt</i>	String to 16 bit integer
<i>StrExtract</i>	Extract substring from string
<i>StrFromMediumInt</i>	Integer to string
<i>StrHash</i>	Return hash value of string
<i>StrReplaceSubStr</i>	Replace substring in string
<i>StrSqueeze</i>	Removes any character from string
<i>StrToLower</i>	Change case of string to lower
<i>StrToUpper</i>	Change case of string to upper

<i>TskDeInit</i>	Deinitialize task
<i>TskDestroy</i>	Deinitialize task and free space
<i>TskExit</i>	Exit task with code
<i>TskExitWithMsg</i>	Exit task after displaying message
<i>TskInit</i>	Initialize task
<i>TskNew</i>	Initialize task and allocate space

Thread

A *Thread (Thr)* is used to represent a single thread-of-control (similar to OS/2). However, MS-DOS implements only single threaded programs, therefore there is only one instance of a *Thr*. The only use threads have currently, is as a mechanism for pushing, popping, and invoking exception handlers (in the Ada style). Typically, a program might set up a single exception handler via *Thr* which traps any program logic errors (are triggered with "asserts"). (See also Task page 11 and Exception page 8)

Tree

A *tree* is a recursive data structure that may contain zero or more children trees and zero or one parent trees.


<i>ThrBadParameter</i>	Signal bad function parameter
<i>ThrClear</i>	Clear thread
<i>ThrDisablePushAndPop</i>	Disable further signaling
<i>ThrDiskFull</i>	Signal disk full
<i>ThrDeInit</i>	Deinitialize thread object
<i>ThrEndOfFile</i>	Signal end of file
<i>ThrEnablePushAndPop</i>	Enable signaling
<i>ThrFatalLogicError</i>	Signal program logic error
<i>ThrInit</i>	Initialize thread object
<i>ThrIsFatalError</i>	Is exception non-recoverable?
<i>ThrIsInitialized</i>	Is thread initialized?
<i>ThrOpSysError</i>	Signal system error
<i>ThrOutOfMemory</i>	Signal out of memory
<i>ThrPopCtx</i>	Pop to previous exception handler
<i>ThrPushErrAndReturn</i>	Invoke current exception handler
<i>ThrPushCtx</i>	Push new exception handler
<i>ThrReturnStatus</i>	Signal status condition
<i>ThrWarning</i>	Signal warning

<i>TreAppChild</i>	Append child(ren)
<i>TreAppSibling</i>	Append sibling(s)
<i>TreAsDll</i>	Return tree as linked list
<i>TreAsLel</i>	Return tree as list element
<i>TreAsObj</i>	Return tree as object
<i>TreClient</i>	Return client of tree
<i>TreClientNextSequential</i>	Return next sequential client tree
<i>TreClientDoAllSuccessors</i>	Do function: all successors
<i>TreClientDoBreadthFirst</i>	Do function: breadth first
<i>TreClientDoBranchDepthFirst</i>	Do function: branch depth first
<i>TreClientDoChildren</i>	Do function: children, forwards
<i>TreClientDoChildrenBkws</i>	Do function: children, backwards
<i>TreClientDoDepthFirst</i>	Do function: depth first
<i>TreClientDoDepthFirstBkws</i>	Do function: depth first, backwards
<i>TreClientDoDescBranchDepthFirst</i>	Do function: descendent branches
<i>TreClientDoDescBreadthFirst</i>	Do function: descendent breadth
<i>TreClientDoDescDepthFirst</i>	Do function: descendent depth
<i>TreClientDoDescDepthFirstBkws</i>	Do function: descendent depth
<i>TreClientDoDescLeaves</i>	Do function: descendent leaves
<i>TreClientDoLeaves</i>	Do function: leaves

Tree

A tree is a recursive data structure that may contain zero or more children trees and zero or one parent trees.
(Continued from page 12)

TreClientDoParentsNearestFirst	Do function: nearest parents first
TreClientDoRange	Do function: range
TreClientDoSuccessors	Do function: successors
TreClientFindChild	Do search function: children
TreClientFirstChild	Return client of first child
TreClientLastChild	Return client of last child
TreClientLastLeaf	Return client of last leaf
TreClientNext	Return client of next sibling
TreClientNextUncle	Return client of next uncle
TreClientParent	Return client of parent
TreClientPrev	Return client of previous sibling
TreClientPrevSequential	Return previous client sequentially
TreCut	Cut node(s) from tree
TreCutChildren	Cut children from tree
TreDeInit	Deinitialize tree object
TreDoAllSuccessors	Do function: successors
TreDoBranchDepthFirst	Do function: branches depth first
TreDoBreadthFirst	Do function: breadth first
TreDoChildren	Do function: children
TreDoChildrenBkws	Do function: children backwards
TreDoDepthFirst	Do function: depth first
TreDoDepthFirstBkws	Do function: depth first backwards
TreDoDescBranchDepthFirst	Do function: descendent branches
TreDoDescBreadthFirst	Do function: descendent breadth
TreDoDescDepthFirst	Do function: descendent depth
TreDoDescDepthFirstBkws	Do function: descendent depth
TreDoDescLeaves	Do function: descendent leaves
TreDoLeaves	Do function: leaves
TreDoRange	Do function: range
TreDoSuccessors	Do function: successors
TreFirstChild	Return first child
TreHasChildren	Does tree have any children?
TreHasSiblings	Does tree have any siblings?
TreInit	Initialize tree object
TrelsChild	Is tree a child?
TrelsDirectAncestor	Is related related to another?
TrelsRoot	Is tree the root?
TreInsChild	Insert child(ren)
TreInsSibling	Insert sibling(s)
TreLastChild	Return last child




Tree

A tree is a recursive data structure that may contain zero or more children trees and zero or one parent trees. (Continued from page 13)

Vertex

A Vertex (Vtx) is used to represent a node in a directed graph (Grf). A vertex can belong to a single graph. It can access each of its incoming (arrow-end) edges (Edg) and each of its outgoing edges. It can also access all its predecessor vertices and successor vertices. (See also Graph page 9 and Edge page 8)

<i>TreLastLeaf</i>	Return last leaf
<i>TreNew</i>	Allocate and initialize tree object
<i>TreNext</i>	Return next sibling
<i>TreNextSequential</i>	Return next sequential tree
<i>TreNextUncle</i>	Return next uncle
<i>TreParent</i>	Return parent
<i>TrePrev</i>	Return previous sibling
<i>TrePrevSequential</i>	Return previous sequential tree
<i>TreSendMsg</i>	Send a int message to client
<i>TreSendGpMsg</i>	Send a ptr. message to client
<i>VtxAddInEdg</i>	Add incoming edge
<i>VtxAddOutEdg</i>	Add outgoing edge
<i>VtxClear</i>	Clear vertex
<i>VtxConnectToGrf</i>	Connect vertex to graph
<i>VtxCountIn</i>	Count incoming edges
<i>VtxCountOut</i>	Count outgoing edges
<i>VtxDisconnect</i>	Disconnect vertex from graph
<i>VtxDoEdge</i>	Do function: all edges
<i>VtxDoEdgeClients</i>	Do function: clients of all edges
<i>VtxDoInEdge</i>	Do function: incoming edges
<i>VtxDoInEdgeClient</i>	Do function: incoming edges
<i>VtxDoOutEdge</i>	Do function: outgoing edges
<i>VtxDoOutEdgeClient</i>	Do function: outgoing edges
<i>VtxDeInit</i>	Deinitialize vertex object
<i>VtxDestroy</i>	Deinitialize vertex object and free
<i>VtxDisconnectFromGrf</i>	Disconnect vertex from graph
<i>VtxFindOutEdg</i>	Do search function: outgoing edges
<i>VtxFindOutEdgClient</i>	Do search function: outgoing edges
<i>VtxGetClient</i>	Return client of vertex
<i>VtxGetFirstIn</i>	Return first incoming edge
<i>VtxGetFirstOut</i>	Return first outgoing edge
<i>VtxGetGraphLel</i>	Return as list element in graph
<i>VtxGetGrf</i>	Return graph
<i>VtxInGrf</i>	Is vertex in graph?
<i>VtxInit</i>	Initialize vertex object
<i>VtxNew</i>	Initialize vertex, allocate space
<i>VtxRemoveInEdg</i>	Remove incoming edge
<i>VtxRemoveOutEdg</i>	Remove outgoing edge
<i>VtxSendClientMsg</i>	Send message to client



/* The following program fragment demonstrates inheritance from the Tree object type. It is not complete but is representative of the use of C+OBJECTS*/

```

struct Node {                                /* Node is a specialized kind of Tree */
    char  *name;                             /* Name for each node */
    Tree  tre;                               /* Node inherits from Tree */
}; typedef struct Node Node;
Node  *pNodR = {0};                         /* The root node */
Class  NodeCls = {0}, *NodTreCls = &NodeCls; /* To inherit from Tree, we need a "class" describing Node */

int  main() {
    NodInitializeModule();                   /* Initialize classes */
    NodBuildTree();                         /* Create a sample set of tree nodes */

    /* "TreClientDo" functions will call a function, NodPrint in these examples,
       and pass the "client" of the tree, a Node pointer in this case, for each tree/node visited */
    /* Print the children nodes of root: a b c */
    TreClientDoChildren( &pNodR->tre, NodPrint ); printf( "\n" ); /* Object-oriented control-structure */
    /* Print the nodes in depth first order: root a.1 a.2 a b c */
    TreClientDoDepthFirst( &pNodR->tre, NodPrint ); printf( "\n" ); /* Object-oriented control-structure */
}

void  NodBuildTree( void ) {                 /* Builds a sample tree of nodes */
    Node *pNod, *pNoda;
    pNodR = NodNew( "root" );               /* Create the root node */
    pNoda = NodNew( "a" );                  NodAppChild( pNodR, pNod );
    pNod = NodNew( "b" );                  NodAppChild( pNodR, pNod );
    pNod = NodNew( "c" );                  NodAppChild( pNodR, pNod );
    pNod = NodNew( "a.1" );                NodAppChild( pNoda, pNod ); /* Note: we are adding to pNoda */
    pNod = NodNew( "a.2" );                NodAppChild( pNoda, pNod ); /* Ditto */
}


Node *NodNew( char *name ) {                /* Allocate memory for a new node and initialize it */
    Node *pNod;
    pNod = (Node *) malloc( sizeof (Node) );
    TreInit( &pNod->tre, NodTreCls, (char *) pNod ); /* Initialize the tree. TreInit needs a class and instance: the "client" */
    pNod->name = name;
}

void  NodAppChild( Node *pNodP, Node *pNodC ) { /* Inherit the Tree function TreAppChild */
    TreAppChild( &pNodP->tre, &pNodC->tre, &pNodC->tre ); /* This adds pNodC as the last child of the parent pNodP */
}

void  NodPrint( Node *pNod ) { /* Print a node name given a Node pointer */
    printf( "%s ", pNod->name );
}

void  NodInitializeModule( void ) { /* Initialize the class which describes Nodes */
    ClsDefaultInit( NodTreCls ); /* DefaultInit uses a default class description */
}

```



TYPE OF LIBRARY:	Object-Oriented Data Structures, Abstract Data Types, Exception Handler, Date and String
Number of Classes:	18
Number of Functions:	over 300
Compilers:	Microsoft C 5.0+ Quick C 2.0+ Turbo C 2.0
Operating Environments:	DOS Windows OS/2 Xenix Sun Unix
Memory Models:	All models
Version:	2.0



*C+Objects is engineered and published by
Objective Systems
Architects and Engineers of Software
2443 Fillmore Street
San Francisco / California / 94115*

C+Objects is a trademark of Objective Systems

PHONE 415/ 929-0964 FAX 415/ 929-8015



C C

C C C